

Megapixel Camera with ExView

- High resolution - 1290 x 960
- 3.75 x 3.75 µm pixel size
- High Sensitivity ExView HAD sensor
- Sony Progressive scan CCD
- Gigabit Ethernet interface
- Very small and light weight



Resolution	1280x960
Sensor Type	1/3" CCD ExView HAD progressive scan Sony ICX445
Pixel Size (µm)	3.75 x 3.75
Maximum Frame Rate	32 fps at 1280x960
Lens Mount	C-mount with adjustable back focus
Digital Interface*	GigE Vision 1.0
Interface Type	IEEE 802.3 1000baseT
Exposure Range	12µs to 60s
Region of Interest (ROI)	Independent x and y control; 1 pixel resolution
Binning	Independent H and V control
Imaging Modes	External Trigger, Fixed frame rate, Software trigger
External Trigger Modes	Rising edge, Falling edge, Any edge, Level high, Level low
External Sync Modes	Trigger ready, Trigger input, Exposing, Readout, Imaging, Strobe, GPO
External Trigger/ Sync Connection	12-pin Hirose
Monochrome Modes	Mono8, Mono16**
Color Modes	Bayer8, Bayer16, RGB24, YUV411, YUV422, YUV444, BGR24, RGBA24, BGRA24
GPIO	1 isolated TTL input, 1 isolated TTL output, 1 non-isolated TTL input, 1 non-isolated TTL output, RS232 I/O
Power Consumption	less than 3 W (12V)
Housing Size	33x46x38 mm
Weight	106 g
Conformity	CE, FCC, RoHS
SDK	Free - includes sample code and driver

About the GC1290 / 1290C

The GC1290 is a 1280x960 resolution CCD camera with Gigabit Ethernet interface (GigE Vision). The GC1290 incorporates a high-quality Sony Exview HAD CCD sensor providing excellent monochrome and color image quality. The GC1290 runs more than 30 frames per second at full resolution and even faster with region of interest readout.

Applications for the GC1290 include:

- industrial inspection
- machine vision
- ophthalmology
- aeronautical and aerospace
- public security
- surveillance
- traffic imaging
- OEM applications

The Prosilica Advantage

- Image quality
- High reliability
- High performance
- Ultra-Compact
- Ease of use and integration
- Rich set of camera features

*GigE Vision™ is a trademark of the Automated Imaging Association

**Mono16 is available on monochrome models only.

Specifications are subject to change without notice

Please refer to the Prosilica web site for a full list of specifications

Prosilica Inc.

101-3750 North Fraser Way | Burnaby, BC | V5J 5E9 | Canada

Tel: 604.875.8855 | Fax: 604.875.8856 | info@prosilica.com

www.prosilica.com

www.adept.net.au