

PRELIMINARY

DATA SHEET

For the most current version visit www.visionresearch.com
Subject to change Rev Nov 2011



Miro M310 shown with optional Remote Control Unit (RCU)

Key Benefits:

WHEN IT'S TOO FAST TO SEE, AND TOO IMPORTANT NOT TO®

You will wonder how we packed so much capability in such a small package! The Phantom Miro M-Series cameras contain all the **high-performance** features you've come to expect from Vision Research in a **compact, rugged camera**.

The Miro M110 and M310 are based on a 1 Megapixel (Mpx), 1280 x 800, custom-designed CMOS sensor from Vision Research. The M110 has 1.6 Gigapixel/second (Gpx/s) throughput, yielding over **1600 frames-per-second (fps)** at full resolution. The M310 doubles that for 3.2 Gpx/s throughput and over **3200 fps at full resolution**. With a 20 micron (µm) pixel size and 12-bit depth, these cameras feature **high-light sensitivity** and **great dynamic range**. Maximum frame rates at reduced resolution are 400,000 fps for the M110 and 650,000 for the M310.

Phantom® Miro® M-Series Digital High-Speed Cameras

Advanced features in a compact camera at an affordable price

Key Features:

- 1 Megapixel and 2 Megapixel custom-designed CMOS sensors
- Up to 3.2 Gigapixels/second throughput
- High light sensitivity
- Compact, rugged design
- Rechargeable battery
- Phantom CineFlash™ storage system
 - 60GB, 120GB and 240GB CineFlash
 - CineFlash Dock
 - eSATA Connectivity



Miro M120 shown with optional BP-U60 battery

Advanced Features:

CineFlash Storage System

Image-Based Auto-Trigger

Burst Mode

Extreme Dynamic Range

Continuous Recording

Auto-Exposure

Measurements

Multi-cine Acquisition

Internal Mechanical Shutter

AutoSet



Miro M-Series Rear View
shown with optional BP-U60 battery

The M120 is based on a >2Mpx sensor and 1.6 Gpx/s throughput. That translates to **730 fps at 1920 x 1200**, or **over 1200 fps at 1152 x 1152**. This camera uses microlenses on its custom-designed CMOS sensor with 10 µm pixel pitch to achieve high light sensitivity. With 12-bit pixel depth, it also sports high dynamic range for excellent image quality. Maximum frame rate at reduced resolution is 400,000 fps.

Depending on model, the minimum digital exposure time is either 1 µs or 2 µs for **sharp, blur-free images** using a global electronic shutter. Vision Research's unique **Extreme Dynamic Range (EDR)** feature is standard on all models. With EDR enabled, each pixel in a frame will receive one of two exposure times – a short exposure for potentially overexposed pixels and a longer exposure for pixels receiving normal light levels. This dramatically increases dynamic range and gets you results even under the most demanding shooting conditions.

For PIV applications, using the Shutter Off mode allows for a **straddle time of 500 ns** on the M110 and M310 and **1.4 µs** on the M120.

An integrated internal mechanical shutter for remote and automatic black references is another unique innovation from Vision Research that comes standard on all models. This means **each shot is properly referenced** for maximum image quality. And, there is no need to manually cap the lens or even touch the camera since the black reference can be done remotely or automatically before each shot.

A **Nikon F-mount is standard on the cameras**. Or, you can choose a C-mount, PL-mount or EOS-mount. The EOS mount enables the use of compatible EF and EF-S lenses. Focus and aperture can be adjusted via our Phantom Remote Control Unit (RCU), Phantom Camera Control software (PCC), or using an adjustment ring on the lens mount. Remote control of focus and aperture is a **huge benefit when cameras are remotely located and/or difficult to reach**.

Each camera model comes in three memory configurations: 3 Gigabytes (GB), 6 GB or 12 GB. The high-speed internal **memory can be segmented** into as many as 16 partitions for cine storage. (A *cine* is Vision Research's raw image format that stores all image data in a compact file.)




Miro M310 Side View



	Phantom Miro M110	Phantom Miro M310	Phantom Miro M120
Maximum Resolution	1280 x 800	1280 x 800	1920 x 1200
Maximum Frame Rate at Maximum Resolution	1630 fps	3260 fps	730 fps
Throughput (Gpx/s)	1.6 Gpx/s	3.2 Gpx/s	1.6 Gpx/s
Sensor Size	25.6mm x 16.0mm	25.6mm x 16.0mm	19.2mm x 12.0mm
Pixel Pitch	20 µm	20 µm	10µm
Minimum Exposure	2 µs	1 µs	1 µs
ISO (12232 SAT Method)	13,000 T Mono 3900 T Color	13,000 T Mono 3900 T Color	4000 Mono 1000 Color

At the end of any shot, save your cine to the removable Phantom CineFlash storage media at about 2.8GB/minute. CineFlash allows you to **save a copy of your cine to non-volatile memory** for later retrieval, and **avoid costly downtime** while you download from camera memory to a computer hard disk. When done with an experiment, just remove the CineFlash from the camera, insert it into its docking station connected to a PC, and drag-and-drop cines from the CineFlash onto your computer disk.

Using PCC, you can then **view, edit, enhance and analyze** cine files. Easily extract still shots, or convert cines into web- and presentation-compatible formats for sharing with colleagues and documenting experiments. Use PCC's measurement tools to **determine distances, angles and speed**. Advanced tools let you **crop, scale, rotate and enhance** cine files to get to the information and insight you seek in images that have never before been seen.



	M110		M310		M120	
	FPS	Secs*	FPS	Secs*	FPS	Secs*
1920 x 1200	N/A	-	N/A	-	730	4.7
1920 x 1080	N/A	-	N/A	-	800	4.8
1152 x 1152	N/A	-	N/A	-	1220	4.9
1024 x 1024	N/A	-	N/A	-	1530	4.9
1280 x 800	1630	4.7	3260	2.3	1600	4.7
1280 x 720	1810	4.7	3630	2.3	1780	4.7
896 x 720	2520	4.9	5040	2.4	2460	5.0
640 x 480	5090	5.1	10100	2.5	4940	5.2
512 x 512	5790	5.2	11500	2.6	5580	5.4
384 x 288	12900	5.6	25900	2.7	12400	5.8
256 x 256	19800	6.1	39700	3.0	18700	6.5
128 x 128	60400	8.0	120700	4.0	55800	8.7
128 x 64	113200	8.6	226300	4.3	107200	9.1
128 x 8	400000	19.5	650000	12.0	400000	19.0

* Record time into maximum memory of 12GB.

PRELIMINARY

DATA SHEET

**Phantom® Miro®
M-Series Digital
High-Speed
Cameras****Additional Features:**

Gb Ethernet

Rechargeable Battery (Sony BP-U30 or BP-U60)

Dimensions: 7.5 x 3.5 x 4 inches, 19 x 9 x 10 cm
(L, W, H without handle or lens)

Weight: 3.0 lbs, 1.4 kg (without CineFlash, battery or lens)

Operating Temperature and Humidity: 0° C to 40° C @
8% to 80% relative humidity, non-condensing

Tiered Service Contracts to protect your investment

Focused

Since 1950, Vision Research has been shooting, designing, and manufacturing high-speed cameras. Our single focus is to invent, build, and support the most advanced cameras possible.

**VISION
RESEARCH**An **AMETEK** Company

100 Dey Road
Wayne, NJ 07470 USA
+1.973.696.4500
phantom@visionresearch.com

www.visionresearch.com

Control your camera with an extensive suite of tools in PCC via a Gb Ethernet connection, or use the Phantom RCU and its **easy-to-learn and easy-to-use touchscreen interface**.

Advanced control signals are available including a Trigger input and Frame Synchronization signal (FSYNC) on the camera back panel. Trigger, Ready, IRIG In, Video Out, IRIG Out and an Auxiliary signal connection are all available on the standard capture cable. The Auxiliary signal can be assigned to Event, Strobe or Memgate.

Video Out is either **NTSC or PAL**. And, a live image is always available in PCC. You can adjust the video to fill the available monitor space for framing a shot, and then switch to a 1:1 pixel representation (center-cropped) for focusing.

Applications for the Phantom Miro M-Series cameras are as broad as your imagination. Study flow dynamics in PIV applications; improve micro- and nano-designs through small object imaging; diagnose and troubleshoot problems with high-speed machinery; improve product designs by characterizing materials and products under stress; any application that demands high-speed image capture at one- to two-megapixel resolution with high light sensitivity is a candidate for the Miro M-Series cameras.

AMETEK Vision Research's digital high-speed cameras are subject to the export licensing jurisdiction of the Export Administration Regulations. As a result, the export, transfer, or re-export of these cameras to a country embargoed by the United States is strictly prohibited. Likewise, it is prohibited under the Export Administration Regulations to export, transfer, or re-export AMETEK Vision Research's digital high-speed cameras to certain buyers and/or end users.

Customers are also advised that some models of AMETEK Vision Research's digital high-speed cameras may require a license from the U.S. Department of Commerce to be: (1) exported from the United States; (2) transferred to a foreign person in the United States; or (3) re-exported to a third country. Interested parties should contact the U.S. Department of Commerce to determine if an export or a re-export license is required for their specific transaction.