

## 1.4 Megapixel CCD Camera with GigE Vision

- Sony 1/2" Progressive scan CCD
- Global shutter (Snapshot shutter)
- Gigabit Ethernet interface
- Asynchronous external trigger and sync I/O
- Region of Interest readout (AOI partial scan)
- Fast frame rates - 20 fps at full-resolution



SMARTER IMAGING FOR BETTER LIVES

Perth: +61 (08) 9242 5411 Sydney: +61 (02) 9905 5551  
Melbourne: +61 (03) 9384 1775

Email: sales@adeptturnkey.com.au  
Web site: www.adept.net.au

<b>Resolution</b>	1360 x 1024
<b>Sensor Type</b>	1/2" CCD Super HAD progressive scan Sony ICX205
<b>Pixel Size (µm)</b>	4.65 x 4.65
<b>Maximum Frame Rate</b>	20 fps at 1360 x 1024
<b>Lens Mount</b>	C-mount with adjustable back focus
<b>Digital Interface*</b>	GigE Vision 1.0
<b>Interface Type</b>	IEEE 802.3 1000baseT
<b>Exposure Range</b>	10µs to 60s
<b>Region of Interest (ROI)</b>	Independent x and y control; 1 pixel resolution
<b>Binning</b>	Independent H and V control
<b>Imaging Modes</b>	External Trigger, Fixed frame rate, Software trigger
<b>External Trigger Modes</b>	Rising edge, Falling edge, Any edge, Level high, Level low
<b>External Sync Modes</b>	Trigger ready, Trigger input, Exposing, Readout, Imaging, Strobe, GPO
<b>External Trigger/ Sync Connection</b>	mini-SMB and 12-pin Hirose
<b>Monochrome Modes</b>	Mono8, Mono16**
<b>Color Modes</b>	Bayer8, Bayer16, RGB24, YUV411, YUV422, YUV444
<b>GPIO</b>	1 isolated TTL input, 3 isolated TTL outputs, RS232 I/O
<b>Power Consumption</b>	3 W (12V)
<b>Housing Size</b>	39x51x63 mm
<b>Weight</b>	175 g
<b>Conformity</b>	CE, FCC, RoHS
<b>SDK</b>	Free - includes sample code and driver

### About the GE1350 / 1350C

The 1.4 Megapixel GE1350 is a high-resolution CCD camera with Gigabit Ethernet interface (GigE Vision\*). The GE1350 incorporates a high-quality Sony 1/2" CCD sensor providing excellent monochrome and color image quality.

### Applications for the GE1350 include :

- industrial inspection
- machine vision
- ophthalmology
- aeronautical and aerospace
- public security
- surveillance
- traffic imaging
- OEM applications

### The Prosilica Advantage

- Image quality
- High reliability
- High performance
- Ultra-Compact
- Ease of use and integration
- Rich set of camera features

\*GigE Vision™ is a trademark of the Automated Imaging Association

\*\*Mono16 is available on monochrome models only

Specifications are subject to change without notice

Please refer to the Prosilica web site for a full list of specifications