



## Genie C1410-2/3

Area Scan Monochrome Cameras



Genie C1410-2/3

### Key Features

- Uses standard PC and server Ethernet ports & hardware
- Supports cable lengths up to 100 m (CAT-5e or CAT-6)
- Simplified set-up with field proven Sapera Essential software featuring CamExpert
- Engineered to accommodate industrial environment with a Ruggedize, screw mount, RJ-45 connector
- Small compact form factor

### Programmability

- Achieve 21.8 fps in full resolution
- Higher frame rates achievable in partial scan mode
- Global electronic shutter with exposure control
- Programmable LUT
- On-board flat-field correction
- On-board Color conversion

### Typical Applications

- Electronics manufacturing inspection
- Food inspection
- Intelligent traffic systems

### Overview

## Small compact GigE Vision camera with uncompromised image quality.

The Genie C1410 uses a Sony CCD, color bayer sensor with a resolution of 1360 x 1024. Operating at 21.8 frames per second at full resolution, the Genie C1410 takes advantage of gigabit Ethernet technology, transmitting data over standard CAT-5e and CAT-6 cables to distances of up to 100 m. Like all Genie cameras, the C1410 is based on AIA (Automated Imaging Association) GigE Vision Standard to directly link the camera to a PC.




### Specifications

Active Resolution	1360 x 1024
Frame Rate	21.8 fps
Pixel Size	6.45 $\mu$ m
Data Format	32-bits, YUV or Raw Bayer
Exposure Control	Programmable, or via External Trigger
Dynamic Range	57 dB
Nominal Gain Range	-6 dB to +12 dB
Output	Gigabit Ethernet, also supports 100 Mbps
I/O Ports	2 opto-isolated input, 2 opto-isolated output,
Lens Mount	C or CS-mount
Size	44 mm x 29 mm x 67 mm (including lens adapter)
Mass	~115 g (without lens)
Operating Temp	0°-45°C
Power Supply	12 V
Power Dissipation	4W
Data Connector	Standard or Screw mount RJ-45
Power and I/O	Hirose 12-Pin
Software Platform	DALSA Sapera LT
GigE Vision Compliant	Yes
Regulatory Compliance	FCC Class A, CE, RoHs 2002/95/EC
Part Number	CR-GEN3-C141x


## Genie C1410-2/3

Area Scan Monochrome Cameras

All Genie cameras feature value added functionality designed specifically for imaging and machine vision applications. All features are easily accessible with DALSA's advanced software tools. These tools deliver superior image capture, performance, and control.



C or CS-mount: 1" diameter  
32 threads per inch



[www.dalsa.com](http://www.dalsa.com)

### Americas

Boston, USA  
Tel: +1 978-670-2000  
sales.americas@dalsa.com

### Europe

Munich, Germany  
Tel: +49 8142-46770  
sales.europe@dalsa.com

### Asia Pacific

Tokyo, Japan  
+81 3-5960-6353  
sales.asia@dalsa.com

DALSA is an international leader in digital imaging and semiconductors and has its corporate offices in Waterloo, Ontario, Canada.

All trademarks are registered by their respective companies. DALSA reserves the right to make changes at any time without notice. © DALSA 2008. genie\_c1410\_2\_3\_102108

